

HCVR-AB Ancillary Board



DESCRIPTION

The HCVR-AB is a Ancillary Board that provides volt free normally open contacts allowing control remotely from the HCVR-3 FACP.

The Ancillary board requires data cable and 24VDC Aux power from the HCVR-3 Releasing FACP

Up to 7 HCVR-AB can be connected to a single HCVR-3 Releasing FACP by using the binary coded DIL switch for addressing.

SPECIFICATIONS

Supply Voltage	20 to 30 VDC
Dimensions	15.1"(W) x 12.2(H) x 3.54"(D)
Board Model	HCVR-AB (Board only)
Enclosure Models	HCVR-ABE-R, HVCR-ABE-C (Enclosure only)
Color	Red or Charcoal
Wiring Length	4000 ft. (RS485)
Standby Current	16 mA
Alarm Current	175 mA
Wiring Gauge	14 to 22 AWG
Relay Contact	30VDC @ 1 Amp (Voltage free change over contact)
Operating Humidity	95% RH (Non-Condensing)
Operating Temperature	23°F to 122°F

STANDARD FEATURES

- UL864 and FM Approved
- Compatible with HCVR-3 FACP
- Four wire connection (data and power)
- Supervised data connection
- Available in Red or Charcoal enclosure (sold separately)

PRODUCT LISTINGS			
SIGNALING  LISTED S6468		California State Fire Marshal 7300-0410:0207	 FM APPROVED 3046396

Specifications subject to change without notice.

